

CLA Series

All models out to the CLA series designed for

- Excellent sound
- Compact size
- Low weight
- versatile
- Versatile setup combinations
- Bi-Amplifier or singal-Amplifier


CLA-881x

A 2-way full range system in a trapezoidal enclosure. Includes dual 8inch(64mm voice coil) Ferrite magnet LF driver and a 1inch(34mm voice coil) Ferrite magnet HF driver with a 90° horizontal horn,80°to 60°vertical horn. This cabinet has a very natural and clear sound which makes it an ideal match for our power mixing console. Combining the CLA-801 with our CLA-155BQ . Subwoofer makes for CLA system with a deep and powerful bass response. The loudspeaker enclosure shall be rectangular in shape. It is constructed with 15mm thickness high-density plywood and employ extensive internal bracing support.



CLA-881x

Full Range




CLA-1001x

A 2-way full range system in a trapezoidal enclosure. Includes dual 10inch(64mm voice coil) Ferrite magnet LF driver and a 2inch(44mm voice coil) Ferrite magnet HF driver with a 90° horizontal horn,80°to 60°vertical horn. This cabinet has a very natural and clear sound which makes it an ideal match for our power mixing console. Combining the CLA-801 with our CLA-18BQ . Subwoofer makes for CLA system with a deep and powerful bass response. The loudspeaker enclosure shall be rectangular in shape. It is constructed with 15mm thickness high-density plywood and employ extensive internal bracing support.



CLA-1001x

Full Range




CLA-1202x

A 2-way full range system in a trapezoidal enclosure. Includes dual 12inch(75mm voice coil) Ferrite magnet LF driver and a 2inch(44mm voice coil) Ferrite magnet HF driver with a 90° horizontal horn,80°to 60°vertical horn. This cabinet has a very natural and clear sound which makes it an ideal match for our power mixing console. Combining the CLA-801 with our CLA-218BQ . Subwoofer makes for CLA system with a deep and powerful bass response. The loudspeaker enclosure shall be rectangular in shape. It is constructed with 15mm thickness high-density plywood and employ extensive internal bracing support.



CLA-1202x

Full Range



CLA Series

Model:	CLA-881x	CLA-1001x	CLA-1202x
System Power Rating	300w AES, 12000w Peak	300w AES, 1200w Peak	400w AES, 1600w Peak
Frequency Range(±3dB)	70Hz-20KHz	70Hz-20KHz	55Hz-20KHz
Impedance	4ohm	8ohm	8ohm
Sound Pressure Level(1w/1m)/max.cont.	96dB/123dB SPL	98dB/125dB SPL	100dB/130dB SPL
Coverage	90° hor,80°to 60°ver	90° hor,80°to 60°ver	90° hor,80°to 60°ver
Transducers LF	2x8inch LF Drivers	10inch LF Drivers	12inch LF Drivers
M/HF	2inch Compression Drivers	2inch Compression Drivers	2inch Compression Drivers
Dimensions wxhxd(Inch)	10.91x25.85x10.56	12.45x19.46x12.68	15.60x24.51x14.85
wxhxd(Millimeter)	277x656x268	316x494x321	396x622x377
Weight(Kg)	19	18	25
Connectors	2 x Neutrik NL4 Speakon	2 x Neutrik NL4 Speakon	2 x Neutrik NL4 Speakon

2 specifications

REAL
Sound