

FLYGEKO壁挂式调光器 / FLYGEKO Wall Rack



WR-12

WR-24

Product Features

- Wall mount design, easy for installing and maintenance
- 220VAC \pm 10%, 50 Hz-60 Hz, single/3 phase 5 lines input
- MCB protection for each channel
- Dual DMX input
- Soft patch available
- Respond time: quick, normal or slow, helping to prolong lamp's life
- 5 User-selectable curves: Liner, Square, S-curve, Extraction or user defined
- 3 working modes: normal, fix and switch
- 50 scenes recordable, manual or auto running
- Keep the last level or auto-run the recorded scenes when signal breaks
- Fade in-out time settable from 0-99.9 seconds
- All channels can be dimmed locally (individually or generally)
- LCD display for easy operation
- External control panel optional
- Wireless infrared remote control and PIR switch
- Support Interface Protocol of central equipments
- Power self-checking warning system, output will be limited once over load or neutral lost to Project the equipment
- RS485, RS-232 & DMX signal optional
- Light weight and elegant outline
- Dimensions: 410X155X821mm(6CH/12CH, LxWxH)
570X155X821mm(24CH, LxWxH)

性能特点

- 采用挂壁式，易于安装，易维护
- 220V \pm 10%, 50/60Hz, 单相/三相五线电源输入
- 每一通道有一个微型断路器MCB保护
- 双DMX信号输入
- 电子配线，灵活设定配接
- 充分延长灯泡寿命，三种灯光负载响应时间：快，中，慢
- 用户可选择5种调光曲线：线性，平方，S-曲线1，开平方，自定义，每一回路可选择不同的曲线
- 三种工作模式：开关、正常、固定
- 可编辑记录50个场景，可手动或自动运行
- 信号中断模式，保持当前场景或自动运行Q场
- 淡入淡出（上升，下降）时间0~99.9秒
- 自带调光功能，回路可单独调节、亦可总升总降
- LCD液晶显示屏显示菜单，操作简便
- 可以选配外接场景按键面板
- 选配无线红外遥控，人体感应开关
- 支持酒店中控设备接口协议，实现智能化控制
- 支持DMX信号、RS485信号、RS232信号
- 外型设计轻巧美观

技术参数

- 工作电压：AC 200V-240V/50-60Hz
- 调光精度：4096级
- 输出电压自动补偿：输入变化10%，输出变化 \leq 1%
- 最小损耗功率：60W
- 输出回路：6路 \times 6KW、12路 \times 4KW、24路 \times 4KW
- 控制信号：2个国际通用协议DMX512输入
- 调光范围：0~100%
- 抗电强度： \geq 2500/1min
- 响应时间：23ms
- 预热值：0~25/255级
- 连续工作时间：24小时
- 防尘、防水等级：IP33
- 产品尺寸：410X155X821mm (6路/12路,长X宽X高)
570X155X821mm (24路,长X宽X高)
- 净重：24.6kg, 37.5kg (24路)

Technical Parameters

- Voltage: 200 ~ 240V AC, 50Hz ~ 60Hz
- Dimming Accuracy: 4096
- Output voltage automatic compensation: 10% change in the input, the output changes \leq 1%
- Minimum loss of power: 60W
- Output: 6CH \times 6KW, 12CH \times 4KW, 24CH \times 4KW
- Control signal: two internationally accepted protocol DMX512 input
- Dimming range: 0 to 100%
- Dielectric strength: \geq 2500 / 1min
- Response time: 23ms
- Preheat value: 0-25 / 255
- Continuous working time: 24 hours
- Dustproof, waterproof rating: Ip33
- Net Weight: 24.6kg, 37.5kg(WR-24)