

FEATURES

- 2 microphone & 3 AUX input
- External microphone panel (**MA-1R**) input
- Treble & Bass tone control
- RMS 25W 8 Ohms mono audio power output
- Acceptable for Dynamic/Condenser Microphone
- Flexible input panel location (Side & Bottom)
- Individual Trim control for 2 microphone input
- Auto override function for central broadcasting (Optional)
- 5~10 second delay for override function



SPECIFICATIONS

| | |
|--------------------|---|
| Power Source | AC 220V/50Hz |
| Power Consumption | 35W |
| Rated Output Power | 25W 8 Ohms |
| Frequency Response | 20 - 20,000Hz ± 3 dB |
| Distortion | Less than 0.2% (Rated Output Power at 1kHz) |
| Tone Control | ± 8 dB at 100Hz, 10,000Hz |
| Input Circuit | |
| Mic 1&2 | -42dB, 600 Ohms, unbalanced |
| Aux 1&2 | -20dB, 10K Ohms, unbalanced |
| External Input | For AVS Mic Panel MA-1R Use Only |
| Speaker Output | 4 - 8 Ohms |
| Dimensions | 270(W) x 185(H) x 70 (D) mm |
| Weight | Approx. 2.6 Kg |

Optional Accessories :



Model : MA-1R (Mic Panel)



Passive Override Module ---- Type A



Active Override Module ---- Type B